

ELMIERE SP 3000

Superior high range water reducer for high strength concrete

Uses

- For piling and mass concrete pour with increased cohesion
- For long haul concrete
- Better pump able concrete
- To be used in high strength concrete for workability retention at low water content.

Advantages

- Better cohesion and particle dispersion minimizes segregation and bleeding
- Improves pump ability
- Chloride free, best for pre-stressed and reinforced concrete
- High range water reducing property allows the production of high strength concrete

Standard complies

ELMEIRE SP 3000 complies with ASTM C 494 Type G and BSEN 934-2:1998

Description

ELMIERE SP 3000 is a chloride free, super plasticizing admixture based on advanced synthetic polymers.

ELMEIRE SP 3000 disperses the fine particles in the concrete mix, enabling the water content of the concrete to perform more effectively.

The very high level of water reduction possible allows major increases in strength.

Properties

Appearance : brown liquid

Specific gravity : $1.18 + /-0.010@20^{\circ}c$

PH value : 7.0

Chloride content : nil to BS 5075

Air entrainment : typically less than

2% additional air is

Entrained at normal

Dosages

Compatibility

ELMIERE SP 3000 is compatible with all types of Portland cements and cement replacement materials such as PFA, GGBFS and Micro silica.

It is also compatible with other ELMRR admixtures used in the same concrete mix.

Dispensing

ELMIERE SP 3000 is introduced in to the mixer with the mixing water. ELMIERE SP 3000 should never be added to dry mix. The admixture works more efficiently if it is added to the dampened mix. Full blending of the admixture and concrete should be ensured by mixing at high speed for a period of at least two minutes.



Typical dosage

For normal concrete, a dosage between 0.75% to 1.5% by weight of cement may be used, and for high strength concrete, dosage between 1.5% to 3% by weight of cement may be used.

The optimum dosage of ELMIERE SP 3000 should always be determined by trial mixes using the materials and conditions that will be experienced in use.

Storage

ELMIERE SP 3000 must be stored in a place where temperature does not drop below +5°c. If product has frozen, thaw at +3°c and agitate until completely reconstituted. Store under cover, out of direct sunlight and protect from extremes of temperature.

Health and safety

ELMIERE SP 3000 does not fall in to the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes.

Splashes on the skin should be removed with water. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately — do not induce vomiting.

Fire

ELMIERE SP 3000 is water based and non-flammable

ELMRR

Elmrr manufactures a broad range of specialist construction chemicals including concrete repair and protection systems, High quality precision grouts, concrete admixtures, Industrial floorings and coatings, technically advanced joint sealants, adhesives, bonding agents, water proofing and damp proofing products, micro concretes and protective coatings.

The wide product range available from elmrr allows it to differentiate itself from many of its competitors. This coupled with its dedication to the pursuit of excellence, innovation and excellent quality, positions elmrr well in the field of construction chemicals

Product Manufactured By:

Elmrr Construction Chemicals (New Rusayl Heights)

FACTORY P.O.BOX 176, PC 124, Rusayl Industrial Area, Muscat, Sultanate of Oman Tel: +968 24446914

Fax: +968 24446776

Email: sales@elmrr.com